

#### HIGH PERFORMANCE BRAKE DRUMS

MTG. TYPE	CENTRIFUSE DRUM PART NO.	BRAKE SIZE	WT. LB.	OVERALL DEPTH	BRAKE SURFACE WIDTH	HUB PILOT DIA.	BOLT CIRCLE DIA.	NO. BOLT HOLES	BOLT HOLE DIA.	DRUM BACK NO.	DRUM BAND NO.	SPECIAL INFORMATION
0	90089BK	15 x 4	64	8.54	4.58	8.78	285.75	10	1.25	91294	91028	
0	88870BK	15 x 4	64	8.94	4.60	9.00	275	8	0.92	91025	91028	Replaces 85369, 85831, 86140, 86909
0	89870BK	15 x 4	65	8.94	4.60	8.78	285.75	10	1.25	91026	91028	
0	90660BK	15 x 4	64	8.94	4.60	8.78	285.75	10	0.96	91029	91028	
0	90174B	15 x 5	78	9.53	5.81	8.78	285.75	10	1.25	90173	87311	
0	91438B	15 x 8.62	90	11.19	9.11	9.00	275	8	0.92	91439	91480	For industry axles except Meritor TN
0	91482B	15 x 8.62	90	11.19	9.11	8.78	285.75	10	0.96	91481	91480	For industry axles except Meritor TN
0	91725B	15 x 8.62	90	11.44	9.11	8.78	285.75	10	0.96	91724	91480	For Meritor TN or TB axle only
0	600001	16.5 x 5	75	8.88	5.46	8.78	285.75	10	1.25	90599	87369	
0	90600B	16.5 x 5	76	9.22	5.82	8.78	285.75	10	1.25	90599	87369	
0	600027	16.5 x 5	78	9.22	5.82	8.78	285.75	10	1.25	620020	87369	OEM specified drum
0	91265B	16.5 x 6	88	9.62	6.68	8.78	285.75	10	1.25	90264	87298	Replaces 91049B
I	87407B	16.5 x 7	85	9.66	7.58	9.44	11.25	10	0.81	88152	87105	Replaces 85369, 85831, 86140, 86909
0	600004HD	16.5 x 7	100	10.41	7.64	8.78	285.78	10	0.96	91538	610021	CentriFuse® HD
0	600084	16.5 x 7	83	10.41	7.64	8.78	285.75	10	0.96	91538	610001	CentriFuse Lite
0	89996B	16.5 x 7	89	10.41	7.64	8.78	285.75	10	0.96	91538	87105	
0	87101B	16.5 x 7	89	10.41	7.64	8.53	11.25	10	0.81	91611	87105	Replaces 86879
0	88797B	16.5 x 7	89	10.41	7.64	9.00	275	8	0.92	88798	87105	
0	6000013HD	16.5 x 8	104	10.91	8.55	8.78	285.75	10	0.96	91793	610023	CentriFuse HD
0	91792B	16.5 x 8	90	10.91	8.55	8.78	285.75	10	0.96	91793	91795	
0	600014HD	16.5 x 8.62	111	11.34	9.10	8.78	285.75	10	0.96	91813	610025	0.375 thick mounting, CentriFuse® HD
0	600026	16.5 x 8.62	100	11.34	9.10	8.78	285.75	10	0.96	91813	6100029	0.375 thick mounting, Replaces 91812B

**NOTES:** All CentriFuse Drums are Balanced  
 I = Inboard Mounted Drum  
 O = Outboard Mounted Drum  
 CA = Check Availability  
 CentriFuse Drum mounting face is 0.25 in thick unless otherwise noted.



*Actual product performance may vary depending upon vehicle configuration, operation, service and other factors. All applications must comply with applicable specifications from Motor Wheel and the respective vehicle manufacturer. Contact Motor Wheel for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.*

Contact Motor Wheel at 855.RIDERED (743.3733) for additional information.